

PRODUCT SPECIFICATIONS OCTOBER 2011- PAGE 1/5

RFL and RSQ Series Stainless Steel Bases

<u>TABLE BASES</u>	COLUMN	SPIDER	COVER SHROUD	STANDARD FINISH ON COVER SHROUD	BOTTOM BASE PLATE	GLIDES	METHOD OF ASSEMBLY	HTS	WTS**
RFL- 18" & 21" DIA.	3" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	2.5MM PRESSED MILD STEEL; 11.8" SQUARE; POWDER COATED FINISH	304 GRADE STAINLESS; 1 MM THICK	SUNRAY (CIRCULAR) FINISH	.35" THICK MILD STEEL; POWDER COATED	1" DIAMETER NYLON; 8MM MILD STEEL THREAD	10MM MILD STEEL THREADED ROD AND NUT	DINING-28.2" COUNTER-34.75" BAR-40.75"	18"- 39LBS NET; 42 LBS GROSS/ 21"- 53LBS NET; 56 LBS GROSS.
RFL- 30" DIA.	4" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	1/4" mild steel flat plate, 19.8" square; POWDER COATED	304 GRADE STAINLESS; 1 MM THICK	SUNRAY (CIRCULAR) FINISH	.35" THICK MILD STEEL; POWDER COATED	1" DIAMETER NYLON; 8MM MILD STEEL THREAD	3 X 8MM COUNTERSUNK SCREWS. FOR TOP; 3 X 10MM FOR BOTTOM. TOOL INCLUDED	DINING-28.2" COUNTER*- 34.75" BAR*- 40.75"	* NET- 118LBS GROSS- 147LB
RSQ- 18x18", 21x21" & 18x27.5" RECTANGLE	2.75" SQUARE 1.35MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	SAME AS RFL 21 & 18" (2 SPIDERS FOR 18" x 27.5" BASE)	304 GRADE STAINLESS; 1 MM THICK	LINEAR; BRUSHED	.35" THICK MILD STEEL; POWDER COATED	1" DIAMETER NYLON; 8MM MILD STEEL THREAD	10MM MILD STEEL THREADED ROD AND NUT	DINING-28.2" COUNTER-34.75" BAR-40.75"	18"- 48LBS NET 51 LBS GROSS. 21"- 63LBS NET 67 LBS GROSS RECTANGLE- 77LBS NET 82LBS GROSS
RSQ- 30" SQUARE	4" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	1/4" mild steel flat plate, 19.8" square; POWDER COATED	304 GRADE STAINLESS; 1 MM THICK	LINEAR; BRUSHED	.35" THICK MILD STEEL; POWDER COATED	1" DIAMETER NYLON; 8MM MILD STEEL THREAD	3 X 8MM COUNTERSUNK SCREWS. FOR TOP; 3 X 10MM FOR BOTTOM. TOOL INCLUDED	DINING-28.2" COUNTER*- 34.75" BAR*- 40.75"	** NET- 137LBS GROSS- 166Lbs
MILAN- 22" x 22"; 22" x 30" & 22" end base	3" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	2.5MM PRESSED MILD STEEL; 11.8" SQUARE; POWDER COATED FINISH	N/A	BRUSHED FINISH	PRESSED STAINLESS STEEL; 304 GRADE; 2.25MM THICK WITH MILD STEEL COMPONENTS	1" DIAMETER NYLON; 8MM MILD STEEL THREAD	10MM MILD STEEL THREADED ROD AND NUT	DINING-28.2" COUNTER-34.75" BAR-40.75"	22" X 22" & 22" X 30"- 7.5 LBS NET; 19 LBS GROSS. END BASE- 11LBS NET 12 LBS GROSS

* FOR BASES WITH 3 X 3" DIA COLUMNS SUBTRACT 5LBS SHIPPING WEIGHT

** FOR BASES WITH 4 X 3" DIA COLUMNS ADD 5LBS SHIPPING WEIGHT

PRODUCT SPECIFICATIONS OCTOBER 2011- PAGE 2/5

<u>TABLE BASES</u>	COLUMN	SPIDER	STANDARD FINISH ON BASE	BOTTOM BASE PLATE	GLIDES	METHOD OF ASSEMBLY	HTS	WTS**
RWG 17" DIA.	2.5" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	2.5MM PRESSED MILD STEEL; 11.8" SQUARE; POWDER COATED FINISH	SUNRAY (CIRCULAR) FINISH	PRESSED 304 GRADE STAINLESS WITH BOLTED IN COUNER WEIGHT TO ADD STABILITY	1" DIAMETER NYLON; 8MM MILD STEEL THREAD	10MM MILD STEEL THREADED ROD AND NUT	DINING-28.2" COUNTER-34.75" BAR-40.75"	17"- 28LBS NET; 33 LBS GROSS
RWG 23.5" DIA.	3" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	2.5MM PRESSED MILD STEEL; 11.8" SQUARE; POWDER COATED FINISH	SUNRAY (CIRCULAR) FINISH	PRESSED 304 GRADE STAINLESS WITH BOLTED IN COUNER WEIGHT TO ADD STABILITY	1" DIAMETER NYLON; 8MM MILD STEEL THREAD	10MM MILD STEEL THREADED ROD AND NUT	DINING-28.2" COUNTER-34.75" BAR-40.75"	23.5"- 35LBS NET; 40 LBS GROSS.
MILAN- 22" x 22" & 22" end base	3" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	2.5MM PRESSED MILD STEEL; 11.8" SQUARE; POWDER COATED FINISH	BRUSHED FINISH	PRESSED STAINLESS STEEL; 304 GRADE; 2.25MM THICK WITH MILD STEEL COMPONENTS	1" DIAMETER NYLON; 8MM MILD STEEL THREAD	10MM MILD STEEL THREADED ROD AND NUT	DINING-28.2" COUNTER-34.75" BAR-40.75"	22" X 22" & 22" X 30"- 7.5 LBS NET; 19 LBS GROSS. END BASE- 11LBS NET 12 LBS GROSS

<u>TABLE BASES</u>	COLUMN	SPIDER	BASE	BASE PLATE	GLIDES	METHOD OF ASSEMBLY	HTS	WTS**
RIVERSTONE- 19.5" DIA.	2.36" DIAMETER; 1.2MM THICK; HIGH POLISHED ALUMINIUM	2.5MM PRESSED MILD STEEL; 11.8" SQUARE; POWDER COATED FINISH	CAST ALUMINIUM	MACHINED TOP SURFACE; BOTTOM AND SIDES ARE POWDERCOAT BLACK	5X1" DIAMETER NYLON; 8MM MILD STEEL THREAD	10MM MILD STEEL THREADED ROD AND NUT	DINING-28.2" COUNTER-34.75" BAR-40.75"	19.5"- 14LBS NET; 19 LBS GROSS/

<u>TABLE BASES</u>	COLUMN	SPIDER	BASE	BASE PLATE	GLIDES	METHOD OF ASSEMBLY	HTS	WTS**
STOPROC 25x25" X BASE	2.36" DIAMETER; 1.2MM THICK; HIGH POLISHED ALUMINIUM OR BLACK POWDERCOAT	2.5MM PRESSED MILD STEEL; 14" SQUARE; POWDER COATED FINISH	CAST ALUMINIUM	CAST ALUMINIUM- POLISHED OR BLACK POWDERCOAT	3X1.5" DIAMETER NYLON; 8MM MILD STEEL THREAD. 1 CAMBERED WHEEL FOR .85" ADJUSTMENT	10MM MILD STEEL THREADED ROD AND NUTS	DINING ONLY-28.2"	25"- 11LBS NET; 16 LBS GROSS

Permanent Mounted Stainless Steel Bases and Counter Supports

<u>TABLE BASES</u>	COLUMN	SPIDER	COVER SHROUD	STANDARD FINISH ON COVER SHROUD	FLOOR MOUNTING PLATE	METHOD OF ASSEMBLY	METHOD OF FASTENING TO FLOOR	HTS
--------------------	--------	--------	--------------	------------------------------------	-------------------------	-----------------------	------------------------------------	-----

Permanent Mounted Stainless Steel Bases and Counter Supports

ECLIPSE BOLT DOWN BASE	3" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	2.5MM PRESSED MILD STEEL; 11.8" SQUARE; POWDER COATED FINISH	304 GRADE STAINLESS; 1 MM THICK	SUNRAY (CIRCULAR) FINISH;	.35" THICK MILD STEEL; POWDER COATED. 4 COUNTERSUNK FASTENING HOLES; .43" IN DIAMETER	10MM MILD STEEL THREADED ROD AND NUT	*** 4 X 3/8" OR 1/2" COUNTERSUNK FASTENERS (NOT INCLUDED).	DINING-28.2" COUNTER-34.75" BAR-40.75"
REOSWELL BOLT DOWN BASE	3" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	2.5MM PRESSED MILD STEEL; 11.8" SQUARE; POWDER COATED FINISH	304 GRADE STAINLESS; 1 MM THICK	SUNRAY (CIRCULAR) FINISH;	.35" THICK MILD STEEL; POWDER COATED. 4 COUNTERSUNK FASTENING HOLES; .43" IN DIAMETER	10MM MILD STEEL BOLT TO SECURE TOP PLATE. BASE IS WELDED TO COLUMN	*** 4 X 3/8" OR 1/2" COUNTERSUNK OR STANDARD FASTENERS (NOT INCLUDED)	DINING-28.2" COUNTER-34.75" BAR-40.75"
STEDDY CORE DRILLED/ GROUT-IN BASE	3" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	2.5MM PRESSED MILD STEEL; 11.8" SQUARE; POWDER COATED FINISH	N/A	N/A	N/A	NO ASSEMBLY REQUIRED	*** REQUIRES A CORE DRILL HOLE FOR A 3" POST. GROUT OR ADHESIVE IS USUALLY USED TO SECURE	DINING-28.2" COUNTER-34.75" BAR-40.75"

*** CONSULT A
PROFESSIONAL FOR
PROPER FASTENING

PRODUCT SPECIFICATIONS OCTOBER 2011- PAGE 4/5

<u>SINGLE LEGS</u>	COLUMN	SPIDER	ADJUSTABLE FOOT	METHOD OF ASSEMBLY	HTS	WTS
KATRINA- 3" DIA	3" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	2.5MM PRESSED MILD STEEL; 7.75" x 9.75; POWDER COATED FINISH	3.35" DIA X .6" THICK CHROME PLATED MILD STEEL COVER OVER A POLYETHELENE FOOT. A 10MM THREAD ALLOWS FOR .5 " OF ADJUSTMENT	SPIDER IS BOLTED WITH 1X10MM BOLT	DINING-28." COUNTER-34.75" BAR-40.75"	DINING- 7LBS NET; 8 LBS GROSS COUNTER- 8 LBS NET; 9 LBS GROSS BAR- 9 LBS NET; 10 LBS GROSS
KATRINA- MINI LEGS ROUND	2" DIAMETER; 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	3.0MM FLAT MILD STEEL; 3.5" x 3.5"; POWDER COATED FINISH	1.5" DIA X .5" THICK CHROME PLATED MILD STEEL COVER OVER A POLYETHELENE FOOT. A 10MM THREAD ALLOWS FOR .5 " OF ADJUSTMENT	SPIDER IS BOLTED WITH 1X10MM BOLT	HEIGHTS AVAILABLE 4", 6", 8"	4"- 2LBS NET; 3 LBS GROSS 6"- 2.5 LBS NET; 4 LBS GROSS 8"- 2.5 LBS NET; 4 LBS GROSS
KATRINA- MINI LEGS SQUARE	2" SQUARE 1.5MM THICK (+/- .2MM) ; 304 GRADE STAINLESS STEEL	3.0MM FLAT MILD STEEL; 3.5" x 3.5"; POWDER COATED FINISH	1.5" DIA X .5" THICK CHROME PLATED MILD STEEL COVER OVER A POLYETHELENE FOOT. A 10MM THREAD ALLOWS FOR .5 " OF ADJUSTMENT	SPIDER IS BOLTED WITH 1X10MM BOLT	HEIGHTS AVAILABLE 4", 6", 8"	4"- 2LBS NET; 3 LBS GROSS 6"- 2.5 LBS NET; 4 LBS GROSS 8"- 2.5 LBS NET; 4 LBS GROSS
TAPERED LEG	2.36" DIAMETER ON TOP, TAPERS TO 1.06" AT BOTTOM 1.2MM THICK MILD	1.6MM PRESSED MILD STEEL; 4.15" x 6.9; POWDER COATED FINISH	1.95" DIA X .5" THICK CHROME PLATED MILD STEEL COVER OVER A	SPIDER IS BOLTED WITH 1X10MM BOLT	DINING-28." COUNTER-34.75"	DINING- 3LBS NET; 4LBS GROSS COUNTER- 4 LBS

PRODUCT SPECIFICATIONS OCTOBER 2011- PAGE 5/5

<u>GLASS ADAPTERS</u>	OVERALL DIAMETER	HEIGHT	FOOTRING TUBE	METHOD OF FASTENING	WTS
GL220	220MM /8.66"	1.31"	MOUNTING PUCK-ALUMINIUM. SPIDER- MILD STEEL POWDER COATED	USE EXISTING 10MM THREADED ROD.	3.5LBS NET 5 LBS GROSS
GL85	85MM /3.346"	MOUNTING SURFACE- .38" BOSS- .3"	MOUNTING PUCK-ALUMINIUM.	10MM COURSE THREADED STUD; 1-3/16" LONG	1 LBS NET 2 LBS GROSS
GL65	65MM / 2.56"	MOUNTING SURFACE- .38" BOSS- .3"	MOUNTING PUCK-ALUMINIUM.	10MM COURSE THREADED STUD; 1-3/16" LONG	1 LBS NET 2 LBS GROSS

<u>FOOTRINGS</u>	OVERALL DIAMETER	HEIGHT	FOOTRING TUBE	METHOD OF FASTENING	WTS
MONZA	15.75"	2.5"	.75" DIA; 1.2mm wall thickness	3 X 1/4" COUNTERSUNK HEX HEAD SCREWS	3.5LBS NET LBS GROSS 5
VOLT	15.75"	9.75"	.75" DIA; 1.2mm wall thickness	3 X 1/4" COUNTERSUNK HEX HEAD SCREWS	4LBS NET LBS GROSS 5